

EN
54-24

100V

Fireproof

Features:

- Distinctive design
- Excellent sound
- IP 65

Description

The compact monitor speaker impresses by a sophisticated design and by its powerful sound. Perfectly suitable for installations where high sound quality is needed.


The 50W powered speaker is equipped with a high quality 2-way system and a 100V transformer with 3 power adjustments. Also, the low impedance operation with 8 ohm is possible. The impact-resistant, UV-resistant ABS plastic housing in white assures enduring stability. For additional reliability, a wetness impregnation of the speaker is provided.

The speaker is also secured with protection class IP 65 against the risks of environmental influences. A comfortable connection of the speaker is made possible by a stable screw terminal with contact protection.


Quick and easy mounting with wall mounting bracket.

Polar Diagrams


Copyright by Four-Audio GmbH & Co KG Licensed to AAC




Copyright by Four-Audio GmbH & Co KG Licensed to AAC



Frequency Response Diagrams



Technical Diagrams



Electrical specifications

Description	MUS-P-50/EN white
Power	50/25/12,5/6,25 (8ohm) W
Impedance (100V)	200/400/800/1600/ ohm
Frequency Range	52 - 24.000 Hz
Frequency Response	48 - 25.000 Hz
SPL, rated noise power / 4m	91,0 dB
Sensitivity EN54-24, 1W/4m	72,8 dB
Sensitivity EN54-24, 1W/1m	84,8 dB
Dispersion -6dB, 500Hz	360° (h) / 360° (v)
Dispersion -6dB, 1KHz	200° (h) / 155° (v)
Dispersion -6dB, 2KHz	110° (h) / 120° (v)
Dispersion -6dB, 4KHz	80° (h) / 25° (v)

Mechanical specifications

Dimensions	326 x 202 x 192 mm
IP Rating	IP65
Weight (net)	3,65 kg
Temperature range	-10 / +55 °C
Mounting	Swivel bracket
Connector	6-pin screw terminal
Terminal diameter	2,5 mm
Max. cable cross section loop	4,9mm ²
Colour	white