



Description

2-way music-horn for Voice Alarm, 30W power, EN 54-24 certified

Mechanical specifications

Rated voice/noise power	30/15/7,5/3,75 W
Dimensions	370x255x291 mm
Colour	RAL 7035
SPL, IEC268-5, 1W1m	98,0 dB
SPL, EN54-24, Pmax 4m	100,0 dB
Sensitivity, EN54-24, 1W4m	86,0 dB
Frequency range, IEC268-5	237 - 21.100 Hz
Frequency response	65 - 24.000 Hz
Dispersion -6dB, 500Hz	190° (h) 205° (v)
Dispersion -6dB, 1000Hz	70 °(h) 90° (v)
Dispersion -6dB, 2000Hz	85° (h) 90° (v)
Dispersion -6dB, 4000Hz	80° (h) 110° (v)

Mounting Instructions:

- 1. Mount the U-bracket on the ceiling with the appropriate screws for the surface.
- 2. If necessary, remove the speaker enclosure from the U-bracket.
- 3. Insert the loudspeaker cable through the cable entry of the previously removed rear wall of the housing.
- 4. Connect the loudspeaker cable to the terminals 100V and COM. If necessary, select a different power tapping.
- 5. Carefully reinsert the back panel into the housing.