



Description

Wall speaker for Voice Alarm, 10W power, EN 54-24 certified

Mechanical specifications

Rated voice/noise power	10/6/3/1,5 W
Dimensions	253x194x82 mm
Colour	white
SPL, IEC268-5, 1W1m	93,0 dB
SPL, EN54-24, Pmax 4m	91,0 dB
Sensitivity, EN54-24, 1W4m	81,0 dB
Frequency range, IEC268-5	197 - 21.900 Hz
Frequency response	175 - 23.500 Hz
Dispersion -6dB, 500Hz	h=180° v=180°
Dispersion -6dB, 1000Hz	h=160° v=160°
Dispersion -6dB, 2000Hz	h=100° v=100°
Dispersion -6dB, 4000Hz	h=60° v=60°

Mounting Instructions:

1. Guide the connection cables through the cut-out in the rear panel of the speaker.
2. Attach the back panel of the speaker to the wall. Use the enclosed screws.
3. Connect the cable to the 100V transformer.
4. Place the loudspeaker housing on one side of the rear wall so that the clamping spring engages in the hole. Press the second clamping spring inwards with a screwdriver and at the same time press the speaker against the wall so that the second clamping spring engages
5. Use the enclosed plastic caps to cover the side holes.

EN 54-24:2008
Ref. Nr.: 007-13
ID-Code: SAA-LS07
 1438-CPR-0924